

## PRODUCT INFORMATION

### REGUPOL EQUILINE BORDER



#### Applications:

Elastic edging elements for riding arenas, paddocks, walkways, washbays and more.

#### Special features and benefits:

Moulded elastic part, straight element with rounded edges and bolt holes (plugs supplied). Plugs made of **REGUPOL** material to cover bolt holes, use a one-component PUR adhesive sealant. Also available as curved 1/8 circle segments.

#### Installation:

Installation with reinforcement steel onto leveled and compacted gravel base. Other options available.

#### Sustainability:

Our **REGUPOL equestrian floors** consist of over 80 % recycled raw materials and have been awarded the label "Top Recycled Product" by the New Life initiative.

#### Material:

PUR binders, components made of synthetic rubber - coloured

#### Dimensions:

1000 x 300 x 150 mm

tolerances: length/width  $\pm 1\%$  | thickness  $\pm 2$  mm

#### Water permeability:


Permeable to water



#### Available colours:



teracotta



black

Deviations from the colours shown are possible due to production batches and display or print reasons.



# PRODUCT INFORMATION

## REGUPOL EQUILINE BORDER



Properties	Standard	Result
Material		PUR binders, components made of synthetic rubber (SBR), coloured
Thickness		150 mm
Dimensions		1,000 × 300 mm
Weight		approx. 40 kg/piece
HIC value	based on the EN 1177 standard	approx. 1.37 m
Impact resistance	based on EN 1517	> 21 Nm
Tensile strength	based on DIN EN ISO 1798	approx. 1.20 N/mm <sup>2</sup>
Elongation at break	based on DIN EN ISO 1798	approx. 90%
Abrasion	based on DIN ISO 4649	approx. 265 mm <sup>3</sup>
Hardness	based on DIN ISO 7619 - 1	approx. 40 Shore A
Migration of certain elements	EN 71-3	passed
Chlorine resistance	based on DIN EN ISO 175	consistent
Temperature resistance	in-house testing	- 30 °C to + 70 °C
Cold breaking resistance	in-house testing	24 h / - 40 °C, no break
Resistance to cold	in-house testing	5 h / - 30 °C, no break